

Application for
UNITED STATES LETTERS PATENT

of

STEPHEN GOLD

and

PETER THOMAS CAMBLE

for

SELF-REPAIRING OPERATING SYSTEM FOR COMPUTER ENTITIES

SELF-REPAIRING OPERATING SYSTEM FOR COMPUTER ENTITIES**Field of the Invention**

The present invention relates computers and particularly to a method of installing an operating system in a computer entity, in the event of a system failure.

Background to the Invention

Headless computer entities are known in the art, and are also known as "headless appliances". A known headless computer entity comprises a data-processor, memory, a plurality on input/output ports or the like, and an operating system. However, headless appliances are generally designed without user interfaces, and lack a keyboard, pointing device e.g. mouse or track ball, and visual display monitor. This has the advantages both of reducing the cost of ownership, since the cost of the user interface hardware need not be borne by the purchaser, and also inhibits interference with the operation of the appliance.

If an operating system failure occurs in some way, either due to data corruption a software bug or the like, then a headless appliance will simply stop functioning, and cannot be repaired manually except by replacing a data storage device, e.g. a system disk, with a new manufactured system disk containing a default operating system and default operating system configuration settings for the whole appliance. Replacement of the disk may involve erasing all data on the appliance. In a headless appliance there is no way that a human administrator of the appliance can directly manually install software updates to an internal operating system, or to application software since there is no system console.

A prior art solution used in headless appliances is to place an operating system in a flash ROM, thereby ensuring that the operating system cannot be easily damaged. This is fine for appliances in which an operating system can be contained in a flash ROM, such as a network attached storage device (NAS).

However, where a headless computer entity is running applications, the operating system is far too large to fit into a flash ROM and has to be stored on a hard disk. Hard disks are vulnerable to corruption and damage and there is a risk of operating system failure where the operating system is stored on a hard disk.

5

A prior art solution for rectifying failure of an operating system stored on a hard disk includes a system developed by Microsoft® and Intel®, in which hardware and BIOS additions to a processor and hard disk ensure that if a running primary operating system fails in any way, for example fails to boot, locks up or crashes, then the BIOS switches to another identical copy of the operating system stored on a hard disk. This system is based on:

10

15

20

25

- An NVRAM message passing interface between a BIOS and the primary operating system, allowing the primary operating system to indicate to the BIOS that it has booted successfully.
- Hardware "watchdog" timers which reset the hardware if the primary operating system fails to clear the timers, so that if the operating system locks, the watchdog timers are not cleared, and the system automatically detects this and resets the BIOS extensions which trigger a boot from a second partition on the hard disk containing a secondary operating system if the primary operating system stored on the first partition fails to boot twice.
- Software to check that the primary operating system fully boots, by monitoring key services provided by the operating system, and making sure that they are running smoothly after boot of the operating system.

30

The concept of an operating system rebuild function in which a secondary operating system rebuilds a primary operating system from a compressed pristine version of the primary operating system is known in the Microsoft\Intel system.

However, this known system assumes that the primary operating system is static and invariant with time.

In the case of computer entities running applications, there are many configuration settings which need to be made and reapplied. Therefore, in a computer entity running applications, there are other parts of software and code beyond the operating system which may need to be included in a full system rebuild following a failure of an operating system. The known rebuild system of Microsoft/Intel does not address the problem of how to rebuild a full system including applications settings in an automated manner, without the requirement for a user console.

The above known approach has the disadvantage and risk of failure if applied to a headless computer entity. In a headless computer entity, there is no way an administrator of the entity can manually install software updates to the operating system or application software. Therefore, the entity needs some mechanism to update the operating system, but when the entity operating system is on disk, it is very difficult for a running operating system to update itself reliably. Further, if a running operating system on a headless entity attempts to update itself, and a fault occurs during an update, then the headless entity will crash and stop working, unless there is an effective automatic operating system rebuild scheme in place, which also restores applications settings.

What is required is an install or rebuild process that is triggered in a variety of ways such that the process can be fully automated or manually controlled depending upon the type of trigger. Additionally, there is a requirement for a rebuild process that is sensitive to the status of the computer entity data, such that if corrupted data is detected as part of the rebuild process this data would be deleted and replaced with uncorrupted default data. Conversely, if the data is uncorrupted the rebuild process would not unnecessarily replace this data with default data.

Summary of the Invention

According to first aspect of the present invention there is provided a method of restoring an operational state of a computer entity, said computer entity comprising:

at least one data processor;

at least one data storage device;

a primary operating system capable of running said computer entity;

a secondary operating system capable of rebuilding said primary operating system; and

a copy of said primary operating system stored on said data storage device;

said method comprising the steps of:

booting said computer entity to operate from said secondary operating system; and

under control of said secondary operating system, rebuilding said primary operating system from said copy of said primary operating system.

According to a second aspect of the present invention there is provided a computer entity comprising:

at least one data processor;

at least one data storage device;

a primary operating system capable of running said computer entity;

a secondary operating system capable of rebuilding said primary operating system during a failure of said primary operating system; and

5 a copy of said primary operating system

According to a third aspect of the present invention there is provided a method of running a computer entity, said computer entity comprising:

10 a data storage device divided into a plurality of partition areas;

a primary operating system stored on a first said partition area;

a secondary operating system stored on a second said partition area;

15 said method comprising the steps of:

storing a back up copy of said operating system on a third said partition area.

20

According to one implementation of the present invention a computer entity, comprises a primary operating system and an emergency operating system. A copy of the primary operating system is stored in an operating system back-up area on a data storage device of the computer entity. A primary operating system install or rebuild involves replacing the primary operating system with a known good pristine copy of the primary operating system stored in the back-up area, followed by an application rebuild.

25

A primary operating system rebuild may be initiated by a variety of triggers, such triggers being for example, the primary operating system: failing to boot, locking up, crashing, or if corrupted data is detected. Additional triggers include

30

a manually initiated reset of the primary operating system, performed via a web administration interface.

Depending upon the triggers initiating the rebuild process and a set of corresponding flags set by the triggering process the primary operating system may be rebuilt such that the computer entity configuration data is preserved, such data being for example, application configuration data, network configuration settings, security configuration settings, or user specific data. Alternatively, if data corruption is detected a different set of flags are set by the triggering of the rebuild process, such that all or part of the existing data is deleted and replaced with factory default data.

In one implementation, the end result following a failure of the primary operating system is that the headless computer entity automatically rebuilds the primary operating system without any user intervention. The computer entity is then ready to continue normal operations without any loss to any application data or application configuration settings. In such a situation the only impact to a user or users of the computer entity is that the system simply goes off-line for a period (in one implementation, approximately 20-30 minutes) before it regains fully operational on-line status.

In a further implementation the end result after a failure of the primary operating system is that the computer entity automatically rebuilds or installs the primary operating system without any user intervention such that all or part of the application data or application configuration settings are replaced with factory default data or default application configuration settings respectively.

Additionally, in the above implementations rebuilds may be controlled manually by a user communicating with the headless computer entity via a suitable web administration user interface.

Within this patent specification the terms install and rebuild are used interchangeable such that each term may be applied to a process by which the primary operating system is reconstructed.

5 **Brief Description of the Drawings**

For a better understanding of the invention and to show how the same may be carried into effect, there will now be described by way of example only, specific embodiments, methods and processes according to the present invention with reference to the accompanying drawings in which:

10

Fig. 1 illustrates schematically in perspective view a headless computer entity;

15

Fig. 2 illustrates schematically details of components of the headless computer entity of Fig.1;

Fig.3 illustrates schematically details of a partition architecture of a hard disk data storage device of the computer entity of Fig. 1;

20

Fig.4 illustrates schematically a logical operating system architecture comprising three operating systems present within the headless computer entity of Fig. 1;

25

Fig. 5 illustrates schematically components of the operating systems and applications used in a self-repairing mode for rebuilding a primary operating system and application configuration settings;

30

Fig. 6 illustrates a flow diagram showing schematically initial process steps of an operating system rebuild process of the computer entity;

Fig. 7 illustrates schematically a plurality of trigger mechanisms which initiate an operating system rebuild process of the computer entity;

Fig. 8 illustrates schematically a flow diagram showing process steps of a rebuild process in which application data is preserved;

5 Fig. 9 illustrates schematically a flow diagram showing further process steps of the rebuild process of Fig. 8;

Fig. 10 illustrates schematically a flow diagram showing yet further process steps of the rebuild process of Fig. 8;

10 Fig. 11 illustrates schematically a flow diagram showing process steps of a rebuild process whereby application data is deleted; and

15 Fig. 12 illustrates schematically a flow diagram showing the final process steps of the data delete rebuild process of Fig. 11.

Detailed Description of the Best Mode for Carrying Out the Invention

20 There will now be described by way of example the best mode contemplated by the inventors for carrying out the invention. In the following description numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent however, to one skilled in the art, that the present invention may be practiced without limitation to these specific details. In other instances, well known methods and structures have not
25 been described in detail so as not to unnecessarily obscure the present invention.

30 In this specification, the term "data storage device", is used to describe any non-volatile data storage device suitable for storage of binary data. The term include conventional hard disk drives. Where the term "disk" or "disk drive", this is a specific example of a data storage device. In principal, the methods and apparatus herein can be applied to any data storage device, and is not restricted specifically to disk drives or disks.

In the best mode, a headless computer entity applies a "self-repairing" method, triggered by an operating system failure, in which a fully automated rebuild of a primary operating system, and associated applications on the computer entity occurs.

The option of triggering an operating system rebuild by manual trigger via a web page interface is also provided, so that a user can manually initiate a primary operating system rebuild. Under manual triggering, the operating system rebuild can either preserve application data and application configuration settings of the computer entity, or delete application data and application settings of the computer entity. A manually initiated rebuild of the primary operating system with application data preserved may be triggered under circumstances which include as an example, where there is a suspected minor corruption of the primary operating system, where other important services provided by the computer entity are still running, but non-critical services provided by the computer entity have ceased to operate correctly.

Where a rebuild operation preserving computer entity data and settings are triggered manually, the procedure followed is similar to that where an automatic rebuild of the primary operating system is triggered, usually as a result of a failure of a primary operating system. Configuration settings of the computer entity are restored after the rebuild, and application data, being data generated by applications running on the computer entity and stored within the computer entity, is unaffected by the rebuild process.

On the other hand, where a rebuild is manually triggered in which the application data is deleted, the application configuration settings are restored, since these are still valid even if the application data is corrupted, however the application data itself is deleted during the rebuild process. The manually triggered primary operating system rebuild with application data delete process may be activated where for example under conditions where there is a

suspected corruption of the application data, and it is required to re-set the application data back to a factory preset default condition.

In each of the three rebuild processes, that is automatic rebuild, manually triggered rebuild with application data preserve and the manually triggered rebuild with application data delete, running of the computer entity is handed over from a primary operating system to a secondary emergency operating system, which has the purpose of rebuilding the primary operating system from a reserve stored copy of the primary operating system. The primary operating system, emergency operating system, and back-up copy of the primary operating system are each stored on different storage device partitions within the computer entity. Once the primary operating system has been rebuilt from the stored back-up copy of the primary operating system, application configuration settings, which are stored in a further data storage device partition in the computer entity, are automatically reapplied. Examples of application configuration settings include networking configuration settings, describing a networking connection of the computer entity with other computer entities; installed user data, describing how many users are installed, and identifying those users; administration security data describing an administration security setup of the computer entity; installed user settings data describing individual settings applied to each of one or a plurality of installed users; and back-up schedule data, describing a type of back-up and a timing schedule for data back-up implemented in the computer entity.

In a normal running mode of the computer entity running under control of the primary operating system, the configuration data, stored in a data storage device partition area different to those used to store the primary operating system is updated either periodically and/or whenever configuration setting data changes. For example, when a new user is added to the computer entity, then the installed user data stored in the further data storage device partition area is automatically updated to reflect the fact that a new user has been installed. Similarly, under normal operation, updates of other configuration data types are stored in the further data storage device partition area. Under fault conditions,

giving rise to a rebuild, the stored configuration data in the further partition is available to rebuild the operating system of the computer entity.

The computer entity configuration settings are archived into a plurality of settings files, and a CHECKsum algorithm is applied to ensure that that archived computer entity configuration setting data is not corrupted, when the computer entity configuration setting data is recovered.

Applications running on the computer entity store data in a dedicated data storage device partition. The application data may either be deleted completely, or retained, depending upon whether a primary operating rebuild operation with application data preserve, or with application data delete is initiated.

Referring to Fig. 1 of the accompanying drawings, there is illustrated schematically in perspective view a headless computer entity 100. The headless computer entity comprises a casing 101 containing a processor, memory, one or more data storage devices and one or more communications ports connectable to a local area network 102; optionally, a small display, for example a liquid crystal display (LCD) 103 giving limited information of the status of the device, for example POWER ON mode, a STAND BY mode, or other modes of operation; a CD ROM drive 104; and optionally a back-up data storage device 105, for example a known DDS tape storage device. The headless computer entity is not provided with console having a monitor, mouse, keyboard or other direct user interface, and does not allow direct interaction with a human operator. In operation, the headless computer entity is intended to be self-managing and self-maintaining, and typically will provide a particular function, for example data storage, within a network environment. An example of a headless computer entity of the type described may include a network attached storage device.

Referring to Fig. 2 herein, there is illustrated schematically an architecture of hardware and firmware components of the headless computer entity 200. The computer entity 200 comprises one or more communications ports 201; one or

more data processing devices 202 as are known in the art; a memory 203 associated with the data processor(s); at least one data storage device 204, for example a hard disk data storage device, or an array of a plurality of hard disk data storage devices e.g. a RAID array; an administration interface 205 optimally in the form of an HTML/XML page display interface; a small display, e.g. a liquid crystal display device 206; a plurality of operating systems 207 as will be described herein after; and one or a plurality of application programs 208 providing functionality to the headless computer entity.

Referring to Fig. 3 herein, there is illustrated schematically a format of data storage device 204, upon which operating system(s) 207 are stored. The data storage device is partitioned into a logical data storage area 300 which is divided into a plurality of partition areas according to the architecture shown. A main division into a primary partition area 300 and a secondary partition area 302 is made. Within the primary partition area are a plurality of partitions including a primary operating system system partition 303 (POSSP), containing key operating system files used to initiate a boot or re-boot of a primary operating system of the computer entity; an emergency operating system system partition 304 (EOSSP) containing files used for booting a secondary, emergency operating system under which the computer entity operates under conditions where the primary operating system is inactive or is deactivated; an OEM partition 305; a primary operating system boot partition 306 (POSBP), which contains a majority of files for the primary operating system and for one or more applications, and from which a boot or re-boot continues after initiation from the primary operating system system partition 303; an emergency operating system boot partition 307 (EOSBP) containing a majority of emergency operating system files, from which the emergency operating system continues to boot after initiation from the EOSSP 304; a primary data partition 308 (PDP) containing an SQL data base 309, and a plurality of binary large objects 310, (BLOBs); a user settings archive partition 311 (USAP) used to store user settings data; a reserved space partition 312 (RSP) typically having a capacity of the order of 4 gigabytes or more; and an operating system back-up area 313 (OSBA) containing a pristine uncorrupted

back-up copy of the primary operating system files 314. The primary operating system system partition 303 and the emergency operating system system partition 304 are small "boot strap" system partitions which are used to start the operating system boot process for the primary or emergency operating system respectively, and then hand over the rest of the operating system boot processed to the primary operating system boot partition 306 or the emergency operating system boot partition 307 respectively, depending upon whether a primary operating system boot or an emergency operating system boot has been initiated. The secondary data partition 302 typically stores a plurality of binary large objects 315. In other implementations the secondary data partition 302, may store SQL database files, in addition to those SQL database files stored on the primary data partition 308.

The user settings archive partition 311 contains an archive of for example, user configuration settings, networking configuration settings, security configuration settings, including user administration names and passwords, TCP/IP addresses and net mask, the system network name, time zone information and application specific configuration settings. The user settings archive partition 311 contains non-default configuration settings that have been changed post-installation of the data storage device 204 e.g. following the creation of the partition architecture as detailed in Fig. 3 and an initial installation of the three operating systems. The purpose of the user settings archive is to provide a source of information to restore the original configuration settings of the computer entity and the applications on the computer entity 100.

The primary operating system files are divided between the primary operating system system partition 303, the primary operating system boot partition 306, the primary data partition 308 and the secondary data partition 302. The emergency operating system files are divided between the emergency operating system system partition 304, the emergency operating system boot partition 307 and if required a suitable data partition. The reserved space partition 312, during normal running of the computer entity in the field, is used as

a "scratch space" area to create temporary files as part of the normal running of applications. This therefore separates out these temporary files from the other data partitions, and ensures that all the available space in the data partitions can be used for application data.

5

The primary data partition 308 and the secondary data partition 302, containing various data and databases, remain untouched when a primary operating system rebuild with data preserve process is triggered.

10

The operating system back-up area also contains "hotfix" software patches which serve as minor software updates. Such patches are typically introduced via a network connection or by means of a floppy disk. A minor update process using such patches is based on known patch installation software, but with inventive modifications as follows:

15

Firstly, basic version checking is performed so that each "hotfix" patch can only be applied into the primary operating system version that it is intended for.

20

Secondly, after the computer entity has rebooted successfully any patch files detected in the operating system back-up area during the primary operating system rebuild process are automatically reapplied at the end of this process. If there are multiple patches present, then they are reapplied in alphabetical main order.

25

A "hotfix" patch represents a portion of code which replaces a portion of the primary operating system such that in the event of a primary operating system failure or defect, a portion of the defective operating system may be replaced with the relevant portion of the primary operating system (i.e. "hotfix" patch) stored in the operating system back-up area.

30

Referring to Fig. 4 herein there is illustrated the three operating systems stored on the data storage device 204. The data storage device 204 comprises

a primary operating system (POS) 400, an emergency operating system (EOS) 401 and a known good pristine copy of the primary operating system 402. The known good uncorrupted copy of the primary operating system comprises, for example, a copy of the primary operating system files 403 and copies of default data of the primary operating system 404. The primary operating system serves as the running or "live" operating system, the emergency operating system comprises a "cut down" version of the primary operating system. If the primary operating system fails, the emergency operating system is configured to rebuild the primary operating system using the known good back-up copy of the primary operating system 402.

The operating system back-up area 313 in addition to containing a copy of the primary operating system files 314, also contains data describing the manufacturing default state of the primary operating system partition and the data partitions.

Referring to Fig. 5 herein, there is illustrated schematically an architecture of operating system 207 and administration interface 205. The operating system and interface comprises a web administration interface 500 allowing access to the computer entity via a page display over a network connection, and allowing a manual reset operation of the computer entity to be instructed from a remote user console; an error detection and reset trigger component 501 for detecting errors or faults in the primary operating system, and triggering a reset operation; a primary operating system restore utility 502 for carrying out a reset operation in response to a trigger signal generated by the error detection trigger component 501, or in response to a command for a reset by a user input via web administration interface 500; a network provisioning component 503 for provisioning other computer entities in a network, e.g. user or client computers; and as described previously, the primary operating system system partition 303; the emergency operating system system partition 304; the operating system back-up area 313; and the user settings archive partition 311.

Referring to Fig. 6 herein there is illustrated initial stages of a rebuild process, initiated by detection of a defect on the data storage device 204 at stage 600. The emergency operating system is triggered at step 601. The various triggers associated with the reboot process described herein are detailed in Fig. 7 below. Following a trigger as detailed in Fig. 7 the emergency operating system is booted at stage 602. There are two ways of booting into the emergency operating system at stage 602, these being firstly via a "fail-over" scheme trigger, which is a BIOS based scheme such that if the primary operating system fails to boot a predetermined number of times e.g. twice, then the BIOS will automatically boot from the emergency operating system system partition. Secondly, the emergency operating system may be booted by software responsive to the triggers detailed in Fig. 7. Following the booting of the emergency operating system at stage 602 specific flags are set to indicate a specific type of rebuild process, at stage 603. Differing rebuild processes include, a rebuild process **preserving** user data and a rebuild process **deleting** user data. An emergency operating system boot counter is reset by the BIOS at stage 604, such that the next boot of the computer entity 100 is from the primary operating system as shown in stage 605. A user of the computer entity 100 is informed of the type of rebuild/update in step 606, such information being displayed via the web administration interface in step 607 and/or a liquid crystal display on the computer entity 100 at stage 608. The primary operating system restore utility is initiated in step 609 and depending upon the flags set at 603, which are determined effectively by the type of trigger (see Fig. 7) the primary operating system restore utility determines the type of rebuild required at 610. The type of flags or indicators set at stage 603 determine a rebuild with data preserve or data delete at stage 611.

Referring to Fig. 7 herein there is illustrated a variety of triggers which are used to initiate the booting of the emergency operating system at stage 602. A first automatic reset with data preserve flag set 700, occurs when the BIOS fail-over scheme is initiated 701. Alternatively, an automatic reset flag for data delete 702 is set when a data disk repair scheme 703 is initiated, such a data disk repair

scheme being initiated when, for example, it has been detected that data on the data storage device 204 is corrupted.

The emergency operating system may be booted following a manually initiated trigger 704 whereby the data delete flag 705 or the data preserve flag 706 may be set in response to a command entered via web administration interface 500. Additionally, the emergency operating system may be booted by software 707 in response to an instruction to perform a software update 708 or in response to an instruction for a tape restore 709. A tape restore may be required when for example, corruption of the back-up data/databases on the data storage device 204 occurs. When performing a tape restore 709 the primary operating system restore utility 502 firstly erases the data of the computer entity and installs the back-up data from the tape. Secondly, the utility should check that the back-up tape media from which the user wishes to restore has the correct data and application name.

Referring to Fig. 8 herein there is illustrated a flow diagram detailing the various stages of the rebuild process in which the data preserved flag has been set. The primary operating system restore utility overwrites selected primary operating system partitions, these being the primary operating system system partition and the primary operating system boot partition at stage 800. The operating system back-up area is used as a source to replace the files to be overwritten in both partitions at stage 801. Following the overwriting of the partitions at stage 800 the system identification (SID) is blank. The result of overwriting the partitions at stage 800, with files from the operating system back-up area, is a copy of the primary operating system being installed into the primary operating system system partition and the primary operating system boot partition at stage 803. The user is informed of the status of the rebuild/update process at 804, such status information being displayed via the web administration interface 500 and/or the liquid crystal display on the computer entity.

The primary operating system restore utility sets a flag in step 805 in the user settings archive partition to indicate that the system reset should restore the user settings 806. The primary operating restore utility checks whether the manual reset flag was set following the boot into the emergency operating system at step 807. If the restore utility detects that the manual flag was set, it sets a further flag to indicate system reset: manual initiation at stages 809 and 810 respectively. Irrespective of the detection of a manual reset flag the primary operating system is rebooted at step 814.

Referring to Fig. 9 herein there is illustrated the latter stages of the rebuild process. At step 900 the primary operating system is in a manufacturing default state, such that it will now set its system identification following this first boot. The restore utility checks the flags for the type of rebuild required at stage 901. Following the protection of reset application specific data 902 and the reset computer entity configuration settings 903 the restore utility checks the flags for "restore user settings" 904. The restore utility proceeds to restore the user settings from the user settings archive partition 311 at step 905. The type of settings include, for example, client account information 906, application configuration settings 907 and administration name/password 908. In addition to resetting the application specific data 905 the restore utility restores the computer entity configuration settings at 909, such settings being for example, the network settings 910 and the network system name 911. The computer entity configuration settings are restored using the network provisioning component 503.

Referring to Fig. 10 herein there is illustrated the final stages of the rebuild process such that following the restoring of the settings the primary operating system reboots at step 1000. The user settings archive 311 is checked for the correct signature at step 1001. When the primary operating system restore utility attempts to retrieve the archive data, a CHECKsum parity check utility checks the signature within the user settings archive to establish if the contents within the

user settings archive (the configuration data etc.) are incorrect. If incorrect the CHECKsum utility notes the particular failure e.g. a failure in the application configuration data, user account information or network configuration settings. In the event of the user settings archive containing an incorrect signature the user/configuration settings are set back to factory defaults at step 1002 and the user is informed of an archive signature failure at step 1003. Also the user is prompted to re-configure the incorrect and/or lost settings at step 1004, such re-configuring being performed by the user via, for example, a web administration interface. Irrespective of the archive signature status the user is informed of the reset trigger type at step 1005, such trigger types being as detailed in Fig. 7 and include an automatic reset. In such instances the automatic reset alert will be displayed to the user via the web administration interface and/or the liquid crystal display at step 1006. If the emergency operating system was booted following a manual reset trigger a user of the computer entity 100 will be informed of a manual reset alert via the web administration interface and/or the liquid crystal display at step 1007. All flags set by the restore utility are cleared at step 1008. Any "hotfix" patches stored in the operating system back-up area will then be automatically reapplied to the newly restored primary operating system at step 1009, such that the newly restored primary operating system contains all updated data and settings prior to the primary operating system failure.

Referring to Fig. 11 herein there is illustrated the stages of the rebuild process whereby the emergency operating system is booted at stage 602 having the data delete flag set.

The primary operating system restore utility overwrites certain primary operating system partitions, these being the primary operating system system partition 303 and the primary operating system boot partition 306 at step 800. The operating system back-up area is used as a source to replace the files to be overwritten in both partitions at step 801. Following the overwriting of the partitions at step 800 the system identification (SID) is blank. The result of the overwriting of the partitions at step 800 with files from the operating system back-

up area result in a copy of the primary operating system being installed into the primary operating system system partition and the primary operating system boot partition at step 803. A user of the computer entity 100 is informed of the rebuild status at 1100. Such rebuild status information being displayed to the user via a web administration interface 500 and/or the liquid crystal display 103 at step 806. Additionally, a user of the computer entity 100 is also informed of the process of deleting the back-up data at step 1101. The primary operating system restore utility then proceeds to erase and recreate the primary data partition at step 1102, the default primary data partition files and the SQL server default database files are restored at 1103 from the operating system back-up area 313 at step 1104. The secondary data partition is recreated at step 1105, and any default data files and SQL server database files are recreated at step 1106. The restore utility sets the relevant flags at 1105 such flags being the "system reset: data delete" flag 1106 and the "system reset: restore user settings" flag 806.

Referring to Fig. 12 herein there is illustrated the final stages of the restore process with data delete. The restore utility checks for a manual reset flag at step 1200. If a manual reset flag is detected the primary operating system restore utility sets a flag 1201, this flag being a "system reset: manual initiation" flag 1202. The primary operating system is then automatically rebooted at step 1203. Following automatic reboot, user settings and application settings are restored, and there is displayed a message on the web administration interface and/or liquid crystal display based on the flags set, which allows a user to tell what type of reset has been performed, as described with reference to Fig. 9 herein before.

A primary operating system rebuild incorporating data delete as detailed in Figs. 11 and 12 may be considered as an emergency rebuild process in the event of a tape restore not being available. Situations in which an operating system rebuild with data delete would be required include the data within the primary data partition and/or the secondary partition and/or data on a second data disk being corrupted. Additionally, the above data delete process may be required

30003760

-21-

when a data storage device 204, being a data disk, has failed due to an error with the disk or its data.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227